

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

Claim Amendments

1-9. (canceled)

10. (previously presented) A beverage bottling plant for filling bottles with a liquid beverage filling material, said beverage bottling plant comprising:

a filling machine being configured to fill empty bottles with liquid beverage filling material;

a conveyer arrangement being configured and disposed to move empty bottles to said filling machine;

said beverage filling machine comprising a plurality of beverage filling positions, each beverage filling position comprising a beverage filling device for filling bottles with liquid beverage filling material;

said filling devices comprising apparatus being configured to introduce a predetermined volume of liquid beverage filling material into the interior of bottles to a substantially predetermined level of liquid beverage filling material;

said apparatus being configured to introduce a predetermined volume of liquid beverage filling material comprising apparatus being

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

configured to terminate the filling of beverage bottles upon liquid beverage filling material reaching said substantially predetermined level in bottles;

a closing station being configured and disposed to close filled bottles;

a conveyer arrangement being configured and disposed to transfer filled bottles from said filling machine to said closing station;

a labeling station being configured and disposed to receive bottles to be labeled;

a conveyer arrangement being configured and disposed to convey bottles to said labeling station;

said labeling station comprising:

a storage being configured and disposed to store a continuous collapsed tube of flat uncut sleeve labels disposed sequentially one after the other;

a mandrel structure;

said mandrel structure being configured to open a continuous collapsed tube of uncut sleeve labels;

said mandrel structure having a receiving end and a

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

discharge end remote from said receiving end;

a first set of roller apparatus being configured and disposed to advance an opened continuous tube of uncut sleeve labels along said mandrel structure from said receiving end towards said discharge end;

said first set of roller apparatus being disposed adjacent said receiving end of said mandrel structure;

a second set of roller apparatus being configured and disposed to advance an opened continuous tube of uncut sleeve labels along said mandrel structure to said discharge end;

said second set of roller apparatus being disposed between said first set of roller apparatus and said discharge end of said mandrel structure;

apparatus being configured and disposed to cut an opened sleeve label from an opened continuous tube of uncut opened sleeve labels to thus produce a cut opened sleeve label for a bottle disposed at said discharge end of said mandrel structure;

said cutting apparatus comprising a rotating disc having at least one sleeve cutting knife operatively connected thereto;

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

each said at least one sleeve cutting knife being configured and disposed to be moved between a position of rest and a position of cutting;

each said at least one sleeve cutting knife comprises a portion configured to move said at least one sleeve cutting knife into the cutting position, and also comprises a structure to move said at least one sleeve cutting knife into the rest position;

said cutting apparatus also comprising at least one electromagnet configured and disposed to move said at least one sleeve cutting knife into the cutting position;

said cutting apparatus being disposed between said first set of roller apparatus and said second set of roller apparatus;

said mandrel structure comprising an expander apparatus being configured and disposed to sufficiently expand a portion of an uncut opened sleeve label, immediately adjacent said cutting apparatus, between said first set of roller apparatus and said second set of roller apparatus, to make taut a portion of an opened tube of uncut opened sleeve labels adjacent said

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

cutting apparatus and thus to minimize bunching of an opened continuous tube of uncut opened sleeve labels on said mandrel structure, and also to maximize precision of the cut being effectuated by said cutting apparatus; and

said second set of roller apparatus also being configured and disposed to remove a cut opened sleeve label from said mandrel structure with sufficient velocity and to position a cut opened sleeve label about a bottle disposed at said discharge end of said mandrel structure, and thus to permit a constant cut of a sleeve label being cut and elevated cutting speeds to afford shorter cycle times;

a gripper arrangement being configured and disposed to grip an opened sleeve label cut by said cutting apparatus and to dispose a cut opened sleeve label about a bottle to be labeled;

said gripper arrangement comprising:

a base structure;

a first gripper jaw and a second gripper jaw;

each gripper jaw being configured to grip a cut opened sleeve in its opened condition;

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116

Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

each gripper jaw being configured to be connected to said base structure;

a first support structure being configured and disposed to connect said first gripper jaw to said base structure;

a second support structure being configured and disposed to connect said second gripper jaw to said base structure;

each support structure comprising a locating bolt being configured and disposed to connect its corresponding support structure for rotation at said base structure and to permit movement of said gripper jaws into a position wherein a cut opened sleeve label is gripped by said gripper jaws and also into a position wherein a cut opened sleeve label is released from said gripper jaws;

each support structure comprising a guide pin being configured and disposed to connect its corresponding gripper jaw portion to its corresponding support structure;

an actuator arrangement being configured and disposed to actuate said guide pins to move said gripper jaws into a position wherein a cut opened sleeve label is gripped by said

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.:NHL-HOL-70
Serial No.: 10/814,624

gripper jaws and also into a position wherein a cut opened sleeve label is released from said gripper jaws;

each gripper jaw having a slot-type passage being configured and disposed to permit adjusting of its corresponding gripper jaw;

each support structure comprising a passage having a diameter;

each gripper jaw slot-type passage being configured to be aligned with its corresponding support structure passage to permit adjustment of its corresponding gripper jaw;

each support structure comprising a stud being configured to be fixedly disposed in said support structure passage and to extend through said gripper jaw slot-type passage of its corresponding gripper jaw to secure its corresponding gripper jaw to its corresponding support structure subsequent to adjustment of a corresponding gripper jaw;

each gripper jaw comprising:

an adjustment structure being configured and disposed to adjust its corresponding gripper jaw between

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116

Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

an initial position and a final position, which final position being a position configured to minimize misalignment of a cut opened sleeve about a bottle to be labeled; and each support structure further comprising:

a securing structure being configured and disposed to secure its corresponding gripper jaw to its corresponding support structure subsequent to movement of each gripper jaw into said final gripper jaw position by its corresponding adjustment structure; and

said labeling station further comprising:

apparatus being configured and disposed to secure a cut opened sleeve label, positioned by said gripper arrangement about a bottle, to the surface of a bottle to be labeled.

11. (previously presented) The beverage bottling plant for filling bottles, according to claim 10, wherein:

said gripper arrangement comprises an arrangement being configured and disposed to move said gripper arrangement to permit positioning of an open sleeve label about a bottle to be labeled.

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

12. (previously presented) The beverage bottling plant for filling bottles, according to claim 11, wherein:

said first gripper jaw and said second gripper jaw are configured and disposed to hold and to release a sleeve label at the inside of a sleeve label.

13. (previously presented) The beverage bottling plant for filling bottles according to claim 12, comprising at least one of (a) and (b), wherein (a) and (b), comprise:

(a) said first gripper jaw and said second gripper jaw are configured to grip one of (i) and (ii), wherein (i) and (ii) comprise:

(i) a shrink-sleeve label; and

(ii) a stretch-sleeve label; and

(b) said adjustment structure comprises at least one of (iii), (iv), (v), and (vi), wherein (iii), (iv), (v), and (vi) comprise:

(iii) a screw being configured and disposed to be in contact with said fixed stud and to move its corresponding gripper jaw between a first position and a second position,

EXPEDITED PROCEDURE

Response Under 37 C.F.R. §1.116

Examiner: Paul R. Durand

Art Unit: 3721

Docket No.: NHL-HOL-70

Serial No.: 10/814,624

which second gripper jaw position being a position configured to minimize misalignment of a cut opened sleeve gripped by said gripper jaws; and

a spring being configured and disposed to exert a bias on said screw and its corresponding gripper jaw;

(iv) a pinion gear and a pinion rack for each gripper jaw;

each said pinion gear with its corresponding pinion rack is configured and disposed to adjust its corresponding gripper jaw to minimize misalignment of a sleeve label about a bottle to be labeled;

(v) a planar spacer element and an abutment structure for each gripper jaw;

each said planar spacer element with its corresponding abutment structure is configured and disposed to adjust its corresponding gripper jaw to minimize misalignment of a sleeve label about a bottle to be labeled; and

said planar spacer element comprises sheet metal;

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.:NHL-HOL-70
Serial No.: 10/814,624

and

(vi) a check structure, a plurality of spacer rings, and a receiver structure configured to receive said spacer rings; and

each said check structure with its corresponding plurality of spacer rings, and with its corresponding receiver structure is configured to adjust its corresponding gripper jaw to minimize misalignment of a sleeve label about a bottle to be labeled.

14-29. (canceled)

30. (previously presented) A method of operating a container filling plant container labeling station having a sleeve label adding arrangement, configured to add a label to a container, said container labeling station comprising:

an arrangement being configured and disposed to open a continuous tube of uncut sleeve labels;

apparatus being configured and disposed to advance a tube of

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

sleeve labels;

apparatus being configured and disposed to cut a sleeve label from a tube of uncut sleeve labels; and

a sleeve label adding arrangement being configured and disposed to add an open sleeve label about a container to be labeled;

said sleeve label adding arrangement comprising:

a sleeve label holding and releasing structure comprising a first portion and a second portion together being configured and disposed to permit holding open of an open sleeve label and to permit releasing of an open sleeve label about a container to be labeled;

said first portion being configured and disposed to hold and to release a first portion of an open sleeve label;

said second portion being configured and disposed to hold and to release a second, different, portion of an open sleeve label; and

an adjustment and securing arrangement being configured and disposed to adjust and then to secure said sleeve label

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

holding and releasing structure in a first position which corresponds to a diameter of a first type of sleeve label for a first type of container, and being configured and disposed to adjust and then to secure said sleeve label holding and releasing structure in a second position which corresponds to a diameter of a second type of sleeve label for a second type of container, which diameter of said second type of sleeve label is different than the diameter of said first type of sleeve label; said method comprising the steps of:

labeling a plurality of a first type of container, wherein said step of labeling said plurality of a first type of container comprises the steps of:

adjusting and then securing said first and second holding and releasing portions with said adjustment arrangement in a first position which corresponds to a diameter of a first type of sleeve label for the first type of container;

opening a continuous, collapsed, uncut tube of the first type of sleeve labels;

EXPEDITED PROCEDURE

Response Under 37 C.F.R. §1.116

Examiner: Paul R. Durand

Art Unit: 3721

Docket No.: NHL-HOL-70

Serial No.: 10/814,624

advancing the continuous tube of the first type of sleeve labels;

cutting a sleeve label from the continuous tube of the first type of sleeve labels;

holding the open sleeve label with said first and second holding and releasing portions;

positioning the open sleeve label about one of the first type of containers with said first and second holding and releasing portions;

releasing the open sleeve label from said first and second holding and releasing portions; and

repeating the above steps for subsequent containers of said plurality of the first type of container;

stopping labeling upon labeling a desired number of said plurality of the first type of container;

selecting a second type of container to be labeled;

labeling a plurality of the second type of container, wherein said step of labeling said plurality of the second type of container comprises the steps of:

adjusting and then securing said first and second holding and releasing portions with said adjustment arrangement in a second position which corresponds to a diameter of a second type of sleeve label for the second type of container, which diameter of the second type of sleeve label is different than the diameter of the first type of sleeve label; and

repeating the steps for placing the first type of sleeve label on said plurality of the first type of container to place the second type of sleeve label on said plurality of the second type of container.

31. (previously presented) The method of operating a container filling plant container labeling station having a sleeve label adding arrangement, according to Claim 30, wherein said method further comprises the steps of:

stopping labeling said plurality of the second type of container;
selecting one of: the first type of container or another type of container different from the first and second types of container to be

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116

Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

labeled;

adjusting and then securing said first and second holding and releasing portions with said adjustment arrangement in a position which corresponds to the diameter of the selected type of sleeve label for the selected type of container; and

repeating the steps for placing the first type of sleeve label on said plurality of the first type of container to place the selected type of sleeve label on a plurality of the selected type of container.

32. (previously presented) The method of operating a container filling plant container labeling station having a sleeve label adding arrangement, according to Claim 31, wherein said sleeve label adding arrangement comprises an arrangement being configured and disposed to move said sleeve label holding and releasing structure to permit positioning of an open sleeve label about a container to be labeled; wherein said method comprises the step of moving said sleeve label holding and releasing structure.

33. (previously presented) The method of operating a container

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.:NHL-HOL-70
Serial No.: 10/814,624

filling plant container labeling station having a sleeve label adding arrangement, according to Claim 32, comprising at least one of: (a), (b), (c), and (d), wherein (a), (b), (c), and (d) comprise:

(a) said adjustment arrangement is configured and disposed to position and then to secure at least one of: (i) said first sleeve label holding and releasing portion, and (ii) said second sleeve label holding and releasing portion, to minimize misalignment of a sleeve label about a container; and

said method comprises the steps of:

positioning and then securing at least one of (i) and (ii) to minimize misalignment of a sleeve label about a container to be labeled;

(b) said first sleeve label holding and releasing portion and said second sleeve label holding and releasing portion are configured and disposed to hold a sleeve label at the inside of a sleeve label and to release a sleeve label; and

said method comprises the steps of:

holding a sleeve label at the inside of a sleeve with said first sleeve label holding and releasing portion and said second

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

sleeve label holding and releasing portion; and

releasing a sleeve label at the inside from said first
sleeve label holding and releasing portion and said second
sleeve label holding and releasing portion;

(c) said adjustment arrangement is configured and disposed to
position and to retain said first holding and releasing portion and
said second holding and releasing portion at a distance from one
another to minimize misalignment of a sleeve label about a container;
and

said method comprises the steps of:

positioning said first holding and releasing portion and
said second holding and releasing portion at a distance from
one another; and

retaining said first holding and releasing portion and said
second holding and releasing portion at a distance from one
another to minimize misalignment of a sleeve label about a
container to be labeled; and

(d) said first and second holding and releasing portions are
configured to be independently adjustable by said adjustment

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

arrangement to permit gripping of one of: a shrink-sleeve label and a stretch-sleeve label;

said adjustment arrangement comprises an arrangement being configured and disposed to secure each holding and releasing portion independently of one another; and

said method comprises the steps of:

adjusting said first holding and releasing portion with said adjustment arrangement to permit gripping of one of: said shrink-sleeve label and said stretch-sleeve label;

adjusting said second holding and releasing portion with said adjustment arrangement to permit gripping of one of: said shrink-sleeve label and said stretch-sleeve label; and

securing said first holding and releasing portion and said second holding and releasing portion with said arrangement being configured and disposed to secure each holding and releasing portion independently of one another.

34. (previously presented) The method of operating a container filling plant container labeling station having a sleeve label adding,

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

according to Claim 33, comprising at least one of (a), (b), (c), and (d) wherein (a), (b), (c), and (d) comprise:

(a) said adjustment arrangement comprises a screw and a stop structure for each holding and releasing portion;

each said screw with its corresponding stop structure is configured and disposed to adjust its corresponding holding and releasing portion to minimize misalignment of a sleeve label about a container;

said method comprises the step of:

rotating a screw against its corresponding stop structure to adjust its corresponding holding and releasing portion to minimize misalignment of a sleeve label about a container to be labeled;

(b) said adjustment arrangement comprises a pinion gear and a pinion rack for each holding and releasing portion;

each said pinion gear with its corresponding pinion rack is configured and disposed to adjust its corresponding holding and releasing portion to minimize misalignment of a sleeve label about a container;

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

said method comprises the step of:

rotating a pinion gear to adjust its corresponding holding
and releasing portion;

(c) said adjustment arrangement comprises a planar spacer
element and an abutment structure for each holding and releasing
portion;

each said planar spacer element with its corresponding
abutment structure is configured and disposed to adjust its
corresponding holding and releasing portion to minimize misalignment
of a sleeve label about a container; and

said planar spacer element comprises sheet metal;

said method comprises the step of:

positioning a planar spacer element against its
corresponding abutment structure to minimize misalignment of a
sleeve label about a container; and

(d) said adjustment arrangement comprises a check structure, a
plurality of spacer rings, and a receiver structure configured to
receive said spacer rings;

each said check structure with its corresponding plurality of

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116

Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

spacer rings, and with its corresponding receiver structure is configured to adjust its corresponding holding and releasing portion to minimize misalignment of a sleeve label about a container;

said method comprises the steps of:

selecting a plurality of spacer rings; and

positioning a plurality of spacer rings on its corresponding receiver structure and against its corresponding check structure.

35-40. (canceled)

41. (currently amended) ~~The~~ A container filling plant container labeling station having a sleeve label adding arrangement, ~~according to Claim 40, wherein~~ configured to add a label to a container, said container labeling station comprising:

an arrangement being configured and disposed to open a continuous tube of uncut sleeve labels;

apparatus being configured and disposed to advance a tube of sleeve labels;

apparatus being configured and disposed to cut a sleeve label

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

from a tube of uncut sleeve labels;

a sleeve label adding arrangement being configured and
disposed to add an open sleeve label about a container to be
labeled; and

said sleeve label adding arrangement comprising:

a sleeve label holding and releasing structure comprising a
first portion and a second portion together being configured and
disposed to permit holding open of an open sleeve label and to
permit releasing of an open sleeve label about a container to
be labeled;

said first portion being configured and disposed to hold
and to release a first portion of an open sleeve label;

said second portion being configured and disposed to hold
and to release a second, different, portion of an open sleeve
label;

an adjustment and securing arrangement being configured
and disposed to adjust and then to secure said sleeve label
holding and releasing structure in a first position which
corresponds to a diameter of a first type of sleeve label for a

EXPEDITED PROCEDURE

Response Under 37 C.F.R. §1.116

Examiner: Paul R. Durand

Art Unit: 3721

Docket No.: NHL-HOL-70

Serial No.: 10/814,624

first type of container in a first labeling process, and being configured and disposed to re-adjust and then re-secure said sleeve label holding and releasing structure in at least a second position which corresponds to a diameter of at least a second type of sleeve label for at least a second type of container in at least a second labeling process, which diameter of the at least second type of sleeve label is different than the diameter of the first type of sleeve label; and

an arrangement being configured and disposed to move said sleeve label holding and releasing structure to permit positioning of an open sleeve label about a container to be labeled;

said adjustment arrangement is configured and disposed to position and then to secure at least one of: (i) said first sleeve label holding and releasing portion, and (ii) said second sleeve label holding and releasing portion, to minimize misalignment of a sleeve label about a container;

said first sleeve label holding and releasing portion and said second sleeve label holding and releasing portion are configured and

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

disposed to hold a sleeve label at the inside of a sleeve label and to release a sleeve label;

said adjustment arrangement is configured and disposed to position and to retain said first holding and releasing portion and said second holding and releasing portion at a distance from one another to minimize misalignment of a sleeve label about a container;

said first and second holding and releasing portions are configured to be independently adjustable by said adjustment arrangement to permit gripping of one of: a shrink-sleeve label and a stretch-sleeve label;

said adjustment arrangement comprises an arrangement being configured and disposed to secure each holding and releasing portion independently of one another;

said adjustment arrangement comprises a screw and a stop structure for each holding and releasing portion;

each said screw with its corresponding stop structure is configured and disposed to adjust its corresponding holding and releasing portion to minimize misalignment of a sleeve label about a container; and

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116

Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

said screw comprises a stud screw and said stop structure comprises a stud.

42. (currently amended) ~~The~~ A container filling plant container labeling station having a sleeve label adding arrangement, ~~according to Claim 39, wherein~~ configured to add a label to a container, said container labeling station comprising:

an arrangement being configured and disposed to open a continuous tube of uncut sleeve labels;

apparatus being configured and disposed to advance a tube of sleeve labels;

apparatus being configured and disposed to cut a sleeve label from a tube of uncut sleeve labels;

a sleeve label adding arrangement being configured and disposed to add an open sleeve label about a container to be labeled; and

said sleeve label adding arrangement comprising:

a sleeve label holding and releasing structure comprising a first portion and a second portion together being configured and

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

disposed to permit holding open of an open sleeve label and to permit releasing of an open sleeve label about a container to be labeled;

said first portion being configured and disposed to hold and to release a first portion of an open sleeve label;

said second portion being configured and disposed to hold and to release a second, different, portion of an open sleeve label;

an adjustment and securing arrangement being configured and disposed to adjust and then to secure said sleeve label holding and releasing structure in a first position which corresponds to a diameter of a first type of sleeve label for a first type of container in a first labeling process, and being configured and disposed to re-adjust and then re-secure said sleeve label holding and releasing structure in at least a second position which corresponds to a diameter of at least a second type of sleeve label for at least a second type of container in at least a second labeling process, which diameter of the at least second type of sleeve label is different than the diameter

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

of the first type of sleeve label; and

an arrangement being configured and disposed to move
said sleeve label holding and releasing structure to permit
positioning of an open sleeve label about a container to be
labeled;

said adjustment arrangement is configured and disposed to
position and then to secure at least one of: (i) said first sleeve label
holding and releasing portion, and (ii) said second sleeve label
holding and releasing portion, to minimize misalignment of a sleeve
label about a container;

said first sleeve label holding and releasing portion and said
second sleeve label holding and releasing portion are configured and
disposed to hold a sleeve label at the inside of a sleeve label and
to release a sleeve label;

said adjustment arrangement is configured and disposed to
position and to retain said first holding and releasing portion and
said second holding and releasing portion at a distance from one
another to minimize misalignment of a sleeve label about a container;

said first and second holding and releasing portions are

EXPEDITED PROCEDURE

Response Under 37 C.F.R. §1.116

Examiner: Paul R. Durand

Art Unit: 3721

Docket No.: NHL-HOL-70

Serial No.: 10/814,624

configured to be independently adjustable by said adjustment arrangement to permit gripping of one of: a shrink-sleeve label and a stretch-sleeve label;

said adjustment arrangement comprises an arrangement being configured and disposed to secure each holding and releasing portion independently of one another;

said adjustment arrangement comprises a pinion gear and a pinion rack for each holding and releasing portion; and

each said pinion gear with its corresponding pinion rack is configured and disposed to adjust its corresponding holding and releasing portion to minimize misalignment of a sleeve label about a container.

43. (currently amended) ~~The~~ A container filling plant container labeling station having a sleeve label adding arrangement, ~~according to Claim 39, wherein~~ configured to add a label to a container, said container labeling station comprising:

an arrangement being configured and disposed to open a continuous tube of uncut sleeve labels;

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

apparatus being configured and disposed to advance a tube of sleeve labels;

apparatus being configured and disposed to cut a sleeve label from a tube of uncut sleeve labels;

a sleeve label adding arrangement being configured and disposed to add an open sleeve label about a container to be labeled; and

said sleeve label adding arrangement comprising:

a sleeve label holding and releasing structure comprising a first portion and a second portion together being configured and disposed to permit holding open of an open sleeve label and to permit releasing of an open sleeve label about a container to be labeled;

said first portion being configured and disposed to hold and to release a first portion of an open sleeve label;

said second portion being configured and disposed to hold and to release a second, different, portion of an open sleeve label;

an adjustment and securing arrangement being configured

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

and disposed to adjust and then to secure said sleeve label holding and releasing structure in a first position which corresponds to a diameter of a first type of sleeve label for a first type of container in a first labeling process, and being configured and disposed to re-adjust and then re-secure said sleeve label holding and releasing structure in at least a second position which corresponds to a diameter of at least a second type of sleeve label for at least a second type of container in at least a second labeling process, which diameter of the at least second type of sleeve label is different than the diameter of the first type of sleeve label; and

an arrangement being configured and disposed to move said sleeve label holding and releasing structure to permit positioning of an open sleeve label about a container to be labeled;

said adjustment arrangement is configured and disposed to position and then to secure at least one of: (i) said first sleeve label holding and releasing portion, and (ii) said second sleeve label holding and releasing portion, to minimize misalignment of a sleeve

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

label about a container;

said first sleeve label holding and releasing portion and said second sleeve label holding and releasing portion are configured and disposed to hold a sleeve label at the inside of a sleeve label and to release a sleeve label;

said adjustment arrangement is configured and disposed to position and to retain said first holding and releasing portion and said second holding and releasing portion at a distance from one another to minimize misalignment of a sleeve label about a container;

said first and second holding and releasing portions are configured to be independently adjustable by said adjustment arrangement to permit gripping of one of: a shrink-sleeve label and a stretch-sleeve label;

said adjustment arrangement comprises an arrangement being configured and disposed to secure each holding and releasing portion independently of one another;

said adjustment arrangement comprises a planar spacer element and an abutment structure for each holding and releasing portion;

each said planar spacer element with its corresponding

EXPEDITED PROCEDURE

Response Under 37 C.F.R. §1.116

Examiner: Paul R. Durand

Art Unit: 3721

Docket No.: NHL-HOL-70

Serial No.: 10/814,624

abutment structure is configured and disposed to adjust its corresponding holding and releasing portion to minimize misalignment of a sleeve label about a container; and

said planar spacer element comprises sheet metal.

44. (currently amended) ~~The~~ A container filling plant container labeling station having a sleeve label adding arrangement, ~~according to Claim 39, wherein~~ configured to add a label to a container, said container labeling station comprising:

an arrangement being configured and disposed to open a continuous tube of uncut sleeve labels;

apparatus being configured and disposed to advance a tube of sleeve labels;

apparatus being configured and disposed to cut a sleeve label from a tube of uncut sleeve labels;

a sleeve label adding arrangement being configured and disposed to add an open sleeve label about a container to be labeled; and

said sleeve label adding arrangement comprising:

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

a sleeve label holding and releasing structure comprising a first portion and a second portion together being configured and disposed to permit holding open of an open sleeve label and to permit releasing of an open sleeve label about a container to be labeled;

said first portion being configured and disposed to hold and to release a first portion of an open sleeve label;

said second portion being configured and disposed to hold and to release a second, different, portion of an open sleeve label;

an adjustment and securing arrangement being configured and disposed to adjust and then to secure said sleeve label holding and releasing structure in a first position which corresponds to a diameter of a first type of sleeve label for a first type of container in a first labeling process, and being configured and disposed to re-adjust and then re-secure said sleeve label holding and releasing structure in at least a second position which corresponds to a diameter of at least a second type of sleeve label for at least a second type of container in

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

at least a second labeling process, which diameter of the at least second type of sleeve label is different than the diameter of the first type of sleeve label; and

an arrangement being configured and disposed to move said sleeve label holding and releasing structure to permit positioning of an open sleeve label about a container to be labeled;

said adjustment arrangement is configured and disposed to position and then to secure at least one of: (i) said first sleeve label holding and releasing portion, and (ii) said second sleeve label holding and releasing portion, to minimize misalignment of a sleeve label about a container;

said first sleeve label holding and releasing portion and said second sleeve label holding and releasing portion are configured and disposed to hold a sleeve label at the inside of a sleeve label and to release a sleeve label;

said adjustment arrangement is configured and disposed to position and to retain said first holding and releasing portion and said second holding and releasing portion at a distance from one

EXPEDITED PROCEDURE
Response Under 37 C.F.R. §1.116
Examiner: Paul R. Durand
Art Unit: 3721

Docket No.: NHL-HOL-70
Serial No.: 10/814,624

another to minimize misalignment of a sleeve label about a container;

said first and second holding and releasing portions are
configured to be independently adjustable by said adjustment
arrangement to permit gripping of one of: a shrink-sleeve label and a
stretch-sleeve label;

said adjustment arrangement comprises an arrangement being
configured and disposed to secure each holding and releasing portion
independently of one another;

said adjustment arrangement comprises for each holding and
releasing portion: a check structure, a plurality of spacer rings, and a
receiver structure configured to receive said spacer rings; and

each said check structure with its corresponding plurality of
spacer rings, and with its corresponding receiver structure is
configured to adjust its corresponding holding and releasing portion
to minimize misalignment of a sleeve label about a container.